


LL MP2 O600-120-40W


PRODUCT SHEET




Product variants



LL MP1 O600-060-15W
LL MP1 O600-084-30W



LL MP1 O1200-120-40W



LL MP2 O1200-240-80W

Public spaces

LL MP is subtle LED luminaire for general lighting with broad applicability, with wide flexibility in light distribution.

The characteristic features are high energy savings and extreme long lifespan.

Features

- LED technology
- Alluminium body with optimal temperature parameters
- Wide choice of special optic covers
- Surface and pendant mounting with adjustable wire accessory
- High energy savings and fast return of investment

Application

- Office
- School
- Retail
- Supermarkets and shopping centers
- Commercial and public halls



TECHNICAL SPECIFICATION

Electrical data

Input voltage	220–240 V AC, 50–60 Hz
Power	40 W
Max. inrush current	53 A, 200 µs, 230 V AC
Driver	Included

Light source

Light source	120 x LED
Exchangeable	no

Photometrical data

Optic	Standard: SO – diffusion cover, FR – fresnel Optional: CL – plexiglass
CCT	Standard: 4.000 K Optional: 3.000 K
CRI	80

Light technical data

Lifespan L70 B20	50.000 hours, Ta 25 ° C
Efficiency	Min. 100 lm / W

Operation conditions

Control	Standard: On / Off Optional: DALI
IP rating	IP20
Operation temperature	-30 ° C to +40 ° C
Cooling	Conventional


Product data

Color	Standard: Natural Optional: Black or RAL
Material	Anodized aluminium

Packing information (preliminary information)

Dimension (box)	620 mm x 70 mm x 60 mm
Weight	1,85 kg

TECHNICAL DRAWING



OPTIONAL ELECTRONIC MODULE

LL MP DALI DRIVER: additional electronic module for DALI control of the luminaire

ORDER CODES

LL MP2 O600-120-40W-SO-40K-C80-I20-NA

LL MP2 O600-120-40W-FR-40K-C80-I20-NA

ACCESSORIES

LL MP ADJ SUSPENSION – 2 m adjustable wire suspension (1 pair)


MOUNTING

Direct on ceiling, wall or suspended with wire




PHOTOMETRY

Optic SO



Optic CL



Optic FR

