


LL STREET ESS70-18-60W

PRODUCT SHEET



Product variants



LL STREET ESS39-08-13W
LL STREET ESS39-08-22W
LL STREET ESS39-09-16W
LL STREET ESS39-09-25W



LL STREET ESS70-16-33W
LL STREET ESS70-16-48W
LL STREET ESS70-18-40W

Street & Urban

LL STREET ESS is designed for energy-efficient lighting for most types of roads in towns and villages. The luminaire can be equipped with electronic modules and controlled and monitored by central control unit.

Features

- LED technology
- Aluminium body with optimal temperature parameters
- Wide choice of special optics
- Special technology of optical part provides improved performance and easy maintenance in comparison with standard luminaires with glass cover
- Maximal reduction of obtrusive light pollution, glare and radiation into the sky
- Precise setting of demanded output power
- High energy savings and fast return of investment

Application



- Major roads and streets
- Parking lots, pedestrian zones
- Tunnels



TECHNICAL SPECIFICATION

Electrical data	
Input voltage	90–305 V AC, 47–63 Hz
Power	60 W
Max. inrush current	cold start 55 A ($t_{width} = 270 \mu s$, 50% I_{peak}), 230 V AC
Class	II
Driver	Included
Light source	
Light source	18 x LED
Exchangeable	no
Photometrical data	
Optic	Standard: AT Optional: WAS, ASY, DWC, ATD, ASD, ASA, ATW, VSM
CCT	Standard: 4.000 K Optional: 3.000 K, 5.000 K
CRI	Standard: 75 Optional: 80, 90
Light technical data	
Lifespan L70 B20	100.000 hours, T_a 15 °C
Efficiency	Min. 100 lm / W
Operation conditions	
Control	Standard: On / Off Optional: IQRF, CLO, DLO, CLO / DLO, PWL
IP rating	IP67
Operation temperature	-30 °C to +40 °C
Cooling	Conventional
Product data	
Body	IK10
Color	Standard: Natural Optional: Black or RAL
Material	Anodized aluminium
Preliminary info	
Dimension (box)	725 mm x 125 mm x 137 mm
Weight	3,75 kg

TECHNICAL DRAWING



OPTIONAL ELECTRONIC MODULE

- LL STREET CLO: additional electronic module for constant light flux during the whole lifetime of luminaire and 10% extra energy saving
- LL STREET DLO: additional electronic module with preprogrammed regime of dimming which ensures dynamic change of light output over one night
- LL STREET CLO/DLO: additional electronic module provides constant light flux during the whole luminaire lifespan and simultaneously has programmed regime of dimming
- LL STREET IQRF: electronic module for wireless control with luminaires diagnostic

ORDER CODES


- LL STREET ESS70-18-60W-AT-40K-C75-NA
- Crosswalks models - special order of optic +/-90 ° or Elliptic optic

ACCESSORIES










- LL STREET WALL BRACKET

MOUNTING

- Side pole Ø 60 mm



PHOTOMETRY



- 0 ° H
- 90 ° H
- max Cd: 305° H